

| | |
|-----------|--|
| Job Name: | |
| Tag# | |



Submittal Data Sheet

FTXS12LVJU / RXS12LVJU

1-Ton Wall Mounted Heat Pump System



Complete warranty details available from your local dealer or at www.daikincomfort.com. To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec. *If product is installed in a commercial application, limited warranty period is 5 years.*

Indoor Specifications

| Airflow Rate (cfm) | Cooling | | Heating | |
|-------------------------------|--------------------------|-----|-------------------|-----|
| | H | M | H | M |
| | L | SL | L | SL |
| | 403 | 307 | 438 | 335 |
| | 205 | 155 | 240 | 212 |
| Sound (dBA) H / M / L / SL | 45 / 37 / 29 / 23 | | 45 / 39 / 29 / 26 | |
| Dimensions (H x W x D) (in) | 11-5/8 x 31-1/2 x 8-7/16 | | | |
| Weight (Lbs) | 22 | | | |

Outdoor Specifications

| Compressor | Hermetically Sealed Swing Type | | | |
|-----------------------------|--------------------------------|-----|---------|-----|
| Refrigerant | R-410A | | | |
| Factory Charge (Lbs) | 2.65 | | | |
| Refrigerant Oil | PVE (FVC50K) | | | |
| Airflow Rate (cfm) | Cooling | | Heating | |
| | H | M | H | M |
| | L | SL | L | SL |
| | 1,183 | 989 | 992 | 840 |
| Sound Pressure Level (dBA) | 49 | | | |
| Dimensions (H x W x D) (in) | 21-5/8 x 30-1/8 x 11-1/4 | | | |
| Weight (Lbs) | 75 | | | |

Efficiency

| Cooling | | Heating | |
|---------|------|---------|------|
| SEER | 23 | HSPF | 12.5 |
| EER | 12.8 | COP | 4.35 |

Performance

| Cooling (Btu/hr) | |
|---------------------------|-------------------------|
| Rated (Min/Max) | 12,000 (4,800 / 12,000) |
| Sensible @ AHRI | 9,250 |
| Moisture Removal gal/h | .5 |
| Standard Operating Range | 50°F – 115°F |
| Extended Operating Range* | 0°F – 115°F |

Rated Cooling Conditions: Indoor: 80°F DB/67°F WB
Outdoor: 95°F DB/75°F WB

*With field settings and wind baffle

| Heating (Btu/hr) | |
|--------------------------|-------------------------|
| 1: @ 47° Rated (Min/Max) | 14,400 (4,400 / 14,400) |
| 2: @ 17° Rated | 9,200 |
| 3: @ 5°: Capacity / COP | 6,430 / 2.95 |
| Operating Range | 5°F – 65°F |

1: Rated Heating Conditions: Indoor: 70°F DB/60°F WB
Outdoor: 47°F DB/43°F WB
2: Rated Heating Conditions: Indoor: 70°F DB/60°F WB
Outdoor: 17°F DB/15°F WB
3: Heating Conditions: Indoor: 70°F DB/60°F WB
Outdoor: 5°F DB/5°F WB

Electrical

| | 208/60/1 | 230/60/1 |
|-----------------------|----------|----------|
| System MCA | 8.75 | 8.75 |
| System MFA | 15 | 15 |
| Compressor RLA | 4.4 | 3.9 |
| Outdoor fan motor FLA | .22 | .22 |
| Outdoor fan motor W | 23 | 23 |
| Indoor fan motor FLA | .15 | .15 |
| Indoor fan motor W | 23 | 23 |

MFA: Max. fuse amps MCA: Min. circuit amps (A) FLA: Full load amps (A)
RLA: Rated load amps (A) W: Fan motor rated output (W)


Piping

| | |
|------------------------------------------|------|
| Liquid (in) | 1/4 |
| Gas (in) | 3/8 |
| Drain (in) | 5/8 |
| Max. Interunit Piping Length (ft) | 65.6 |
| Max. Interunit Height Difference (ft) | 49.2 |
| Chargeless (ft) | 32.8 |
| Additional Charge of Refrigerant (oz/ft) | .21 |

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)


FTXS12LVJU Dimensional Data



Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

RXS12LVJU Dimensional Data



Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Optional Accessories



| Indoor Unit | | |
|-------------|----------------|-----------------------------------------------------------------------------|
| Included | Part Number | Description |
| | AZAI6WSCDKB | DKN Residential Cloud Wi-Fi Adaptor for Single- and Multi-Zone System (S21) |
| | AZAI6WSPDKC | DKN Plus Interface |
| | DTST-ONE-ADA-A | Daikin <i>One+</i> Smart Thermostat for Ductless Products |
| | BRC944B2 | Wired Remote Controller |
| | BRCW901A08 | Wired Remote Controller Cable – 25ft |
| | BRCW901A03 | Wired Remote Controller Cable – 10ft |
| | DACA-CP1-1 | Inline Condensate Pump (Fits inside all Daikin wall & floor mount units) |
| | DACA-CP4-1 | External Condensate Pump |
| | KRP928BB2S | Interface Adaptor for DIII-NET |

| Description | | |
|-------------|-------------|-------------------------------------------------------------|
| Included | Part Number | Description |
| | DACA-WB-3 | Powder-Coated Wall-Mounted Bracket |
| | KEH041A41 | Drain Pan Heater RXS09_12LV |
| | KKP937A4 | Drain Plug for OD Unit |
| | KPW937F4 | Low Ambient Wind Baffle / Air Adjustment Grille (09/12 MBH) |