

UP TO 2 HEAT / 1 COOL HEAT PUMP


Product Features:

PSP2152

- Battery or system powered
- 5+2 day programmable thermostat
- 2-Heat/1-Cool for use with heat pumps
- Extremely simple to operate and features a large, easy to read, backlit, digital display
- Fahrenheit or Celsius display
- Compatible with 4 wire systems
- Aux heat indicator
- Bi-color LED indicator glows green or red to indicate cooling or heating
- Service filter indicator
- Sleek styling and white color blend beautifully into any decor
- Easy access front battery compartment

PSP2100

- Battery or system powered
- 2-Heat/1-Cool
- Non-programmable
- For use with heat pumps
- Extremely simple to operate and features a large, easy to read digital display
- Fahrenheit or Celsius display
- Compatible with 4 wire systems
- Aux heat indicator
- Sleek styling and white color blend beautifully into any decor
- Bi-color LED indicator glows green or red to indicate cooling or heating
- Easy access front battery compartment



* Complete warranty details available from your local branch.

TERMINAL DESIGNATIONS

Terminal Designations	
R	24 VAC Return
G	Fan Relay
W1	2 nd Stage Auxiliary Heat
Y1	1 st Stage Compressor Relay
O	Reversing Valve (ener. heat)
B	Reversing Valve (ener. cool)
C	24 VAC Common

PRODUCT SPECIFICATIONS

Product Specifications: PSP2100 & PSP2152 Conventional (2H/2C) or Heat Pump (2H/1C)	
Electric Rating:	20-28VAC, 5 VA Max or (2) AA batteries
Output Rating:	Y1, W1, G, O, B – 500 mA
Control Range:	35° - 99° F (2° - 36° C)
Control Accuracy:	+/- 2° F (+/- 1° C)
Outputs:	Y1, G, W1, O, B